

pixels at the same time. Non-interlaced displays are also called Progressive Displays. Normally, Interlaced displays have twice the refresh rate of a non-interlaced display. Interlaced displays are usually marked with an “i”, and Non-interlaced or



An Interlaced Frame draws lines alternately

Progressive displays are marked “NI” or “P”. Besides monitors, media devices like DVD players and TVs are also similarly marked.

4.1.15 LCD

Liquid Crystal Display technology uses an array of liquid crystals sandwiched between two sheets of polarised filters to control the amount of light generated by a cold cathode tube allowed to pass through to the front of the screen. The polarising filters are arranged in different directions of polarity, so that the light coming through one filter will be completely blocked by the other, in the absence of the layer of liquid crystals. The shape of the liquid crystal influences the amount of light passing through the second filter. By varying the voltage applied to the liquid crystal, its shape can be controlled. In colour LCDs, one pixel is made up of three liquid crystals, each coloured Red, Green, or Blue.

4.1.16 Native Resolution

This refers to the actual number of pixels in an LCD. Unlike CRTs, an LCD can only offer maximum clarity if the incoming signal is of the same resolution as the native resolution.

4.1.17 Passive Matrix LCD

This is the older type of LCD, and is still used in smaller displays. Here, the liquid crystals making up the display are addressed by their row and column number, and each row and column has a single controlling circuit. This form of addressing doesn't allow