

To create a torrent file, select Create New Torrent under the File menu. The data file or folder needs to be identified. Piece size can be set manually or set to auto. The tracker URL needs to be provided. A list of public trackers can be easily downloaded from the Net, or the torrent can



The Scheduler in µTorrent has a host of options

be created without one—in which case other means to discover peers will be used. Clicking on Start Seeding will load the torrent once the hashing is complete. Initial Seeding is a special mode of seeding, which can be activated from the torrent's Properties link (available in the context menu). Rather than randomly upload pieces to peers, in the Initial Seeding mode, the emphasis is on selectively uploading pieces so that all the pieces are available among the peers the quickest. This ensures that the superseed does not have to wait till at least one peer gets the entire data.

µTorrent allows the system to be shut down based on the status of torrents using the Auto Shutdown option under the Options menu.

4.2.3 Configuration

µTorrent can be further configured with the Preferences option under the Options menu. Here, under the Connections link, you can specify the maximum bandwidth to be allocated for µTorrent for downloading and uploading. Under the BT link, you can specify the number of connections that are permitted. You can also enable the use of DHT and other methods to find peers sharing the data file. Local Peer Discovery is a method that gives preference to peers that are geographically closer, since this improves data transfer speeds (within a given connection type). Under the Queuing link, you can specify the number of active transfers. If more torrents than this fig-