

handlers such as `onmouseover` and `onclick` can be assigned to any SVG graphical object.

SVG images, being XML, contain many repeated fragments of text and are particularly suited for compression. Once an SVG image has been compressed, it may be referred to as an “SVGZ” image, with the corresponding filename extension. The resulting file may be as small as 20% of the original size.

The use of SVG on the Web is in its infancy. There is a great deal of inertia due to the long-time use of pure raster formats and other formats like Adobe Flash or Java applets, and browser support for SVG is still uneven. However, there are available a number of third-party plug-ins available for SVG.

4.3. Corners And Points In Vector Graphics

A vector image consists of the anchor points and the segments that join them. A single set of anchor points and segments is a contour and an individual vector object may consist of one or more contours and is called a path.

Segments can be either straight or curved, and anchor points define segment ends. Bezier curves are a compact way of mathematically describing a curved segment, which are based on the location of the anchor points that define the segment’s ends and on direction lines that describe the angle and length of the curve.

Anchor points come in two basic types, those with curves and those without curves. A sharp corner is called a cusp. A cusp or corner point’s curve handles can be manipulated totally independent of each other. That is, moving one has no effect on the other. The asymmetric and symmetric anchor points are called smooth curves. In the case of asymmetric points, the control handles can be lengthened or shortened independent of each other. However, if you try changing the direction of one, then