

I Hate ./

Q It is irritating having to type `./` every time I want to run a software. Can't I simply run the binary without the `./` like in the DOS prompt?

A The simplest way to be able to run applications without a `./` is to install or copy the binaries into the `/usr/bin` directory. You can also add a custom path with your applications by editing the `.bashrc` file in your home directory. Add an entry `export export PATH=/home/your_username/your_path:${PATH}` where `/home/your_username/your_path` is the path to where you have installed the binaries.

Firefox Doesn't Open URLs In Mails

Q The links in my mails aren't clickable. I can click on them, but nothing happens. I end up copying the URL and pasting it on my browser—Firefox. How do I get Firefox to automatically open the links when I click them?

A Firefox hasn't been set as the default browser, and therefore, isn't picking up on any of the Web links you click on. To make Firefox your default browser, first start Firefox. Now open up Firefox's Preferences. Click on the Advanced tab and check the box for Always check to see if Firefox is the default browser on startup. Click the Check now button.

If this doesn't work, click on `System > Preferences > Preferred Applications`.

Make sure `Open link in default browser` is checked.

Convert NTFS To EXT3

Q I have a 50 GB NTFS partition that I want to be an EXT3, so I can use it within Linux. How do I do it?

A Boot into the LiveCD and use Gparted from the LiveCD on the NTFS partition. Just make sure you backup all your data from the NTFS partition, because once you format you will not be able to recover any of the data.