

with the file name specified in `PathNameWithoutExtension`. If you use this option, cipher ignores all of the other options.

`/w: PathName:` Removes data on unused portions of a volume. `PathName` can indicate any directory on the desired volume. If you use this option, cipher ignores all of the other options.

Comp

Compares the contents of two files or sets of files byte by byte. Used without parameters, comp prompts you to enter the files to compare.

Syntax:

```
comp [ data1] [ data2] [ /d] [ /a] [ /l] [ /n=number] [ /c]
```

`data1:` Specifies the location and name of the first file or set of files you want to compare. You can use wildcard characters (* and ?) to specify multiple files.

`data2:` Specifies the location and name of the second file or set of files you want to compare. You can use wildcard characters (* and ?) to specify multiple files.

`/d:` Displays differences in decimal format. (The default format is hexadecimal.)

`/a:` Displays differences as characters.

`/l:` Displays the number of the line on which a difference occurs, instead of displaying the byte offset.

`/n= number:` Compares the first number of lines of both files, even if the files are different sizes.

`/c:` Performs a comparison that is not case-sensitive.

Compact

Displays and alters the compression of files or directories on NTFS partitions. Used without parameters, compact displays the compression state of the current directory.

Syntax:

```
compact [{ /c|/u}] [ /s[:dir]] [ /a] [ /i] [ /f] [ /q]  
[ FileName[ ...]]
```