

/c: Compresses the specified directory or file.
/u: Uncompresses the specified directory or file.
/s:dir: Specifies that the requested action (compress or uncompress) be applied to all subdirectories of the specified directory, or of the current directory if none is specified.
/a: Displays hidden or system files.
/i: Ignores errors.
/f: Forces compression or uncompression of the specified directory or file. This is used in the case of a file that was partly compressed when the operation was interrupted by a system crash. To force the file to be compressed in its entirety, use the **/c** and **/f** parameters and specify the partially compressed file.
/q: Reports only the most essential information.
FileName: Specifies the file or directory. You can use multiple file names and wildcard characters (* and ?).

Copy

Copies one or more files from one location to another.

Syntax:

```
copy [ /d ] [ /v ] [ /n ] [ { /y | -y } ] [ /z ] [ { /a | /b } ]  
Source [ { /a | /b } ] [ + Source [ { /a | /b } ] [ + ... ] ]  
[ Destination [ { /a | /b } ] ]
```

/d: When copying an encrypted file, decrypts the copy.
/v: Verifies that new files are written correctly.
/n: Uses a short file name, if available, when copying a file with a name longer than eight characters, or with a file extension longer than three characters.
/y: Suppresses prompting to confirm that you want to overwrite an existing destination file.
/-y: Prompts you to confirm that you want to overwrite an existing destination file.
/z: Copies networked files in restartable mode.
/a: Indicates an ASCII text file.
/b: Indicates a binary file.