

label: Specifies the name for the volume.

/MP: Specifies that the volume should be treated as a mount point or volume name.

volume: Specifies the drive letter (followed by a colon), mount point, or volume name. If a volume name is specified, the **/MP** parameter is unnecessary.

Netstat

Displays active TCP connections, ports on which the computer is listening, Ethernet statistics, the IP routing table, IPv4 statistics (for the IP, ICMP, TCP, and UDP protocols), and IPv6 statistics (for the IPv6, ICMPv6, TCP over IPv6, and UDP over IPv6 protocols). Used without parameters, netstat displays active TCP connections.

Syntax:

```
netstat [-a] [-e] [-n] [-o] [-p Protocol] [-r] [-s] [Interval]
```

-a: Displays all active TCP connections and the TCP and UDP ports on which the computer is listening.

-e: Displays Ethernet statistics, such as the number of bytes and packets sent and received. This parameter can be combined with **-s**.

-n: Displays active TCP connections, however, addresses and port numbers are expressed numerically and no attempt is made to determine names.

-o: Displays active TCP connections and includes the process ID (PID) for each connection. You can find the application based on the PID on the Processes tab in Windows Task Manager. This parameter can be combined with **-a**, **-n**, and **-p**.

-p Protocol: Shows connections for the protocol specified by Protocol. In this case, the Protocol can be **tcp**, **udp**, **tcpv6**, or **udpv6**. If this parameter is used with **-s** to display statistics by protocol, Protocol can be **tcp**, **udp**, **icmp**, **ip**, **tcpv6**, **udpv6**, **icmpv6**, or **ipv6**.

-s: Displays statistics by protocol. By default, statistics are shown for the TCP, UDP, ICMP, and IP protocols. If the IPv6 protocol for Windows XP is installed, statistics are shown for the TCP over IPv6,