

UDP over IPv6, ICMPv6, and IPv6 protocols. The `-p` parameter can be used to specify a set of protocols.

`-r`: Displays the contents of the IP routing table. This is equivalent to the `route print` command.

`Interval`: Redisplays the selected information every `Interval` seconds. Press `CTRL+C` to stop the redisplay. If this parameter is omitted, `netstat` prints the selected information only once.

Net Services

Many services use networking commands that begin with the word `net`. Get a list of all available `net` commands by typing `net/?` at a command prompt.

Example:

```
net start
```

Pagefileconfig.vbs

Enables an administrator to display and configure a system's paging file Virtual Memory settings. Changes a system's existing paging file Virtual Memory settings.

Syntax:

```
pagefileconfig[ .vbs] /change [ /s Computer [ /u  
Domain\User [ /p Password]]] {[ /iInitialPageFileSize]  
[ /m MaximumPageFileSize]} /vo {VolumeLetter|*}  
[ /vo {VolumeLetter2|*} [ ...]]
```

`/s Computer`: Specifies the name or IP address of a remote computer (do not use backslashes). The default is the local computer.

`/u Domain \ User`: Runs the script with the account permissions of the user specified by `User` or `Domain\User`. The default is the permissions of the current logged on user on the computer issuing the command.

`/p Password`: Specifies the password of the user account that is specified in the `/u` parameter.

`/i InitialPageFileSize`: Specifies the new initial size (in MB) to use for the paging file specified.