

/m MaximumPageFileSize: Specifies the new maximum size (in MB) to use for the paging file specified.

/vo { VolumeLetter |*} : Specifies the volume or volumes of the paging file settings to be changed. The volume is specified by a letter followed by a colon (for example, "C:").

Ping

Verifies IP-level connectivity to another TCP/IP computer by sending Internet Control Message Protocol (ICMP) Echo Request messages. Ping is the primary TCP/IP command used to troubleshoot connectivity, reachability, and name resolution.

Syntax:

```
ping [-t] [-a] [-n Count] [-l Size] [-f] [-i TTL]
[-v TOS] [-r Count] [-s Count] [{-j HostList | -k
HostList}] [-w Timeout] [TargetName]
```

-t: Specifies that ping continue sending Echo Request messages to the destination until interrupted. To interrupt and display statistics, press CTRL-BREAK. To interrupt and quit ping, press CTRL-C.

-a: Specifies that reverse name resolution is performed on the destination IP address. If this is successful, ping displays the corresponding host name.

-n Count: Specifies the number of Echo Request messages sent. The default is 4.

-l Size: Specifies the length, in bytes, of the Data field in the Echo Request messages sent. The default is 32. The maximum size is 65,527.

-f: Specifies that Echo Request messages are sent with the Don't Fragment flag in the IP header set to 1. The Echo Request message cannot be fragmented by routers in the path to the destination. This parameter is useful for troubleshooting path Maximum Transmission Unit (MTU) problems.

-i TTL: Specifies the value of the TTL field in the IP header for Echo Request messages sent. The default is the default TTL value for the host. For Windows XP hosts, this is typically 128. The maximum TTL is 255.