

-v **TOS**: Specifies the value of the Type of Service (TOS) field in the IP header for Echo Request messages sent. The default is 0. TOS is specified as a decimal value from 0 to 255.

-r **Count**: Specifies that the Record Route option in the IP header is used to record the path taken by the Echo Request message and corresponding Echo Reply message. Each hop in the path uses an entry in the Record Route option. If possible, specify a Count that is equal to or greater than the number of hops between the source and destination. The Count must be a minimum of 1 and a maximum of 9.

-s **Count**: Specifies that the Internet Timestamp option in the IP header is used to record the time of arrival for the Echo Request message and corresponding Echo Reply message for each hop. The Count must be a minimum of 1 and a maximum of 4.

-j **HostList**: Specifies that the Echo Request messages use the Loose Source Route option in the IP header with the set of intermediate destinations specified in HostList. With loose source routing, successive intermediate destinations can be separated by one or multiple routers. The maximum number of addresses or names in the host list is 9. The host list is a series of IP addresses (in dotted decimal notation) separated by spaces.

-k **HostList**: Specifies that the Echo Request messages use the Strict Source Route option in the IP header with the set of intermediate destinations specified in HostList. With strict source routing, the next intermediate destination must be directly reachable (it must be a neighbor on an interface of the router). The maximum number of addresses or names in the host list is 9. The host list is a series of IP addresses (in dotted decimal notation) separated by spaces.

-w **Timeout**: Specifies the amount of time, in milliseconds, to wait for the Echo Reply message that corresponds to a given Echo Request message to be received. If the Echo Reply message is not received within the time-out, the "Request timed out" error message is displayed. The default time-out is 4000 (4 seconds).

TargetName: Specifies the destination, which is identified either by IP address or host name.