

## SC

Communicates with the Service Controller and installed services. `SC.exe` retrieves and sets control information about services. You can use `SC.exe` for testing and debugging service programs.

### Syntax:

```
sc /command [ ServiceName]
```

### Commands:

**Query:** Queries the status for a service, or enumerates the status for types of services.

**Queryex:** Queries the extended status for a service, or enumerates the status for types of services.

**Start:** Starts a service.

**Pause:** Sends a PAUSE control request to a service.

**Interrogate:** Sends an INTERROGATE control request to a service.

**Continue:** Sends a CONTINUE control request to a service.

**Stop:** Sends a STOP request to a service.

**Config:** Changes the configuration of a service (persistent).

**Description:** Changes the description of a service.

**Failure:** Changes the actions taken by a service upon failure.

**Qc:** Queries the configuration information for a service.

**Qdescription:** Queries the description for a service.

**Qfailure:** Queries the actions taken by a service upon failure.

**Delete:** Deletes a service (from the registry).

**Create:** Creates a service. (adds it to the registry).

**Control:** Sends a control to a service.

**Sdshow:** Displays a service's security descriptor.

**Sdset:** Sets a service's security descriptor.

**GetDisplayName:** Gets the DisplayName for a service.

**GetKeyName:** Gets the ServiceKeyName for a service.

**EnumDepend:** Enumerates Service Dependencies.

The following commands don't require a service name:

**Boot (ok | bad):** Indicates whether the last boot should be saved as the last-known-good boot configuration

**Lock:** Locks the Service Database

**QueryLock:** Queries the LockStatus for the SCManager Database