

/s Computer: Specifies the name or IP address of a remote computer (do not use backslashes). The default is the local computer.

/u Domain \ User: Runs the command with the account permissions of the user specified by `User` or `Domain\User`. The default is the permissions of the current logged on user on the computer issuing the command.

/p Password: Specifies the password of the user account that is specified in the `/u` parameter.

/fi FilterName: Specifies the types of process(es) to include in or exclude from termination.

Tracert

Determines the path taken to an Internet or intranet destination by sending Internet Control Message Protocol (ICMP) Echo Request messages to the destination. The path displayed is the list of near-side router interfaces of the routers in the path between a source host and a destination. The near-side interface is the interface of the router that is closest to the sending host in the path.

Syntax:

```
tracert [ -d] [ -h MaximumHops] [ -j HostList] [ -w  
Timeout] [ TargetName]
```

-d: Prevents `tracert` from attempting to resolve the IP addresses of intermediate routers to their names. This can speed up the display of `tracert` results.

-h MaximumHops: Specifies the maximum number of hops in the path to search for the target (destination). The default is 30 hops.

-j HostList: Specifies that Echo Request messages use the Loose Source Route option in the IP header with the set of intermediate destinations specified in `HostList`. With loose source routing, successive intermediate destinations can be separated by one or multiple routers. The maximum number of addresses or names in the host list is 9. The `HostList` is a series of IP addresses (in dotted decimal notation) separated by spaces.

-w Timeout: Specifies the amount of time in milliseconds to wait for the ICMP Time Exceeded or Echo Reply message corre-