

denounced. Here Adobe recommends that we should use the **MovieClip.framesloaded** property.

It can check if the contents of a specified frame are available locally.

int(value:Number) : Number

It has been denounced since Flash Player 5 to favor `Math.round()`. It can convert a decimal number to an integer value and it is done by truncating the decimal value.

isFinite(expression:Object) : Boolean

It is used to evaluate expression and to return either true if it is a finite number or false if it is infinity or negative infinity.

isNaN(expression:Object) : Boolean

It can evaluate the parameter and can return true value if the value is NaN. This value can not be a number.

length(expression:String, variable:Object) : Number

It has been denounced since Flash Player 5. This function as well as all the string functions have been denounced. According to the recommendation of Macromedia we should use the methods of the String class and the String.Length property in order to perform the same operations.

It can return the length of a specific string or variable.
loadMovie(url:String, target:Object, [method:String]) It can load an SWF or a JPEG file into Flash Player when the original SWF file is playing.

loadMovieNum(url:String, level:Number, [method:String])

It can load an SWF or a JPEG file into a level in Flash Player when the SWF file that is originally loaded is playing.

loadVariables(url:String, target:Object, [method:String])

It read data from an external file as a text file or a text that is generated by ColdFusion, a CGI script, Active Server Pages (ASP), PHP, or Perl script, and it can set the values for variables in a target movie clip.