

cale. The full screen is set to true while the allow scale is set to false. Next the method `loadVariablesNum` loads the txt document named `welcome.txt`.

- Insert seven more keyframes in this layer.
- Next select the second keyframe and type the following script:

```
stop();  
loadVariablesNum("intro.txt", 0);  
unloadMovie(image_mc);  
unloadMovieNum(3);
```

- The above code first loads the text file named 'intro.txt'. The code also unloads the empty movie clip known as `image_mc` with the help of the `unloadMovie` method.
- Now click the third keyframe and type the following script :

```
stop();  
unloadMovieNum(3);  
this.createEmptyMovieClip("image_mc", 2);  
image_mc._x=340;  
image_mc._y=120;  
loadMovie("images\\interface.jpg", image_mc);
```

- In the above code, the `unloadMovieNum` method unloads the movie clip from layer 3. Next an empty movie clip is created in layer 3 by the `createEmptyMovieClip` method. The x and the y coordinates of this movie clip are then set. Lastly the `loadMovie` method loads the `interface.jpg` image
- Now click the fourth keyframe and type the following script :

```
stop();  
unloadMovie(image_mc);  
loadMovieNum("page3.swf", 3);
```

- The above code first unloads the empty movie clip, `image_mc` and then loads the swf file named `page3.swf` in the third layer