

ling the visibility and properties of the methods that are created by the programmer. This helps with the control of access specifiers. However it is to be noted that we can create our own namespaces.

Before understanding the working of a namespace, one should remember that the name of a property or a method always contains two parts, the identifier and a namespace. Consider the following code segment.

```
class Sample
{
    var sampleGreet:String;
    function sampleFunction () {
        trace(sampleGreet + " from
sampleFunction()");
    }
}
```

When a definition is not preceded by a namespace attribute, the names are qualified by a default internal namespace. This implies that they are visible to callers belonging to the same package. In the code snippet above, both the `sampleGreet` and `sampleFunction ()` have an internal namespace value.

Operators

In Flash ActionScripting, operators play a major role. They are basically special functions that work on one or more operands and return a suitable value. The value may be a literal, a variable or an expression that is used as an input by the operator.

For instance, take the following code. Here the addition (+) and the multiplication (*) operator are used with three literal operands (2,3,4) to return a value which is further used by the assignment operator to assign the returned value to the variable `sumNumber`.

```
var sumNumber:uint = 2 + 3 * 4; // uint = 14
```

Various types of operators are used in Flash ActionScripting. The most common operators that are used include the unary, binary or the ternary operator. In the case of the unary operator, one operand is taken (the increment or ++ operator) while in the