

```
        return this;
    }
}
var myTest:Check = new Check();
trace(myTest.thisValue() == myTest); // output:
true
```

We can control the inheritance of instance by using the keywords `override` and `final`. The `override` feature can be used in order to redefine an inheritance method. We can also use the `final` attribute in order to stop the subclass from overriding a method.

4.1 Bound Methods

Bound methods are the methods that are taken out from the instance of this method. It is often called method closure. The methods that are passed as arguments to a function as well as the methods that are returned as values from a function are the examples of bound method. As we have already discussed in our earlier section, ActionScript 3.0 includes some new features and the bound method is no exception here. In ActionScript 3.0 a bound method has similarities to a function as it can hold the lexical atmosphere even when you separate it from its instance.

We must now want to know the basic difference between the bound method and the function closure. Let us now look at those differences:

- In a bound method, the ‘this’ reference for a bound method is always linked with the instance in which the method is implemented. It is always linked with the parent object by which the method is implemented.
- In a function closure the ‘this’ reference is always nonspecific. It indicates that it can point to any object with which the function is associated at the time when it is called.

We need a detailed understanding of the bound method if we use the ‘this’ key word. The ‘this’ key word always gives a reference to the parent object of the method. If we are an ActionScript programmer then we always expect that the ‘this’ key word will refer to that particular class or object that includes the method’s defini-