

```
trace(myCataloglength); // Displays: 3
myRemark = ["firsrt option", "second option",
"third option"];
trace(myRemark.length); // Displays: 3, the num-
ber of // elements, not
the number of words or characters
frameLabels = new Array(24); // Note the sin-
gle numeric //argument used with the Array( ) con-
structor
trace(frameLabels.length); // Displays: 24
```

The 'length' property of an array always maintains a certain rule, such as, it is always one greater than the index number of its last element. Say the indices of an array are 0,1,2,3,4. Suppose the index 4 has a length of 5. On the other hand an array includes elements where the indexes are 0,1,2,3,4 and here the index 60 includes a length of 61.

Another thing that we should always remember is that the last element of an array is always `myArray[myArray.length - 1]`. This is so as the index numbers start from 0 and not from 1.

While attempting any changes in an array the changes are also incorporated in the 'length' property so that the changes are reflected. These changes include adding as well as removing elements from an array. The 'length' property can be set in order to add or remove elements at the end of an array.

By using the 'length' property of an array, a loop can be created and here the loop can access all the elements of an array. In any programming language this kind of looping using the elements of an array is a very basic task.

Example:

Look at the example below, where we have given code to search an array:

```
// Create an Array
var soundtracks = ["mechanical", "hip hop",
"pop", "other", "unique"];
// Check each element to see if it contains "hip
hop"
```