

data i.e. numbers, Booleans, strings, array objects. At the same time it is sometimes left empty. While debugging an application these index numbers are used. We have just discussed that the array 'length' property will return the value in addition to the index number. If the index number is 6 then the length will return 7. It indicates that 6 undefined values can be inserted into the arrays.

Here we have given an example that shows how we can create a new array and how we can delete an item from the required index. At the same time it shows the way we can add as well as replace data at the required index of an array:

```
var monthArr:Array = new Array("Jan", "Feb",  
"Mar", "Apr", "May", "Jun", "Jul", "Aug", "Sep",  
"Oct", "Nov", "Dec");  
delete monthArr[6];  
trace(monthArr); // Jan, Feb, Mar, Apr, May, Jun,  
undefined, Aug, Sep, Oct, Nov, Dec  
trace(monthArr.length); // 12  
monthArr[6] = "JUL";  
trace(monthArr); //Jan, Feb, Mar, Apr, May, Jun,  
Jul, Aug, Sep, //Oct, Nov, Dec
```

Though we have deleted the item from index 6, the array length does not change here and it remains 12. One thing that we should not forget here is that the array index does not disappear from here, rather it turns to a blank string.

6.7 Multidimensional Arrays

Up to now we have been discussing the single dimensional array. In a spreadsheet the single dimensional arrays include a single row or a single column. Now let us discuss multidimensional arrays. In order to create a multidimensional array we need to create arrays within arrays. We can define these as nested arrays. To put it simpler we can say that a multidimensional array is created when in an array the array elements are nothing but arrays themselves.