

```
cout<<"calculate is "<<temp; /* will print 100 */
}
void cal2(void)
{
    int calculate;
    for(calculate=1; calculate<10; calculate++)
        cout<<'.' ;
}
```

The output of the program will be:

```
.calculate is 100
```

Here, 'calculate' is declared as a global variable. This means that it can be accessed by any function in the program. 'calculate' is initialized with 100 in the function `main()`. Next, its value is assigned to the variable 'temp' in the function `cal1()`. Subsequently, a variable 'calculate' is declared in the function `cal2()`, which is a local variable for the `cal2()` function.

We should always remember that C++ is a case-sensitive programming language and hence we should always be careful while naming a variable. The variable names are called identifiers. They may be a single letter, multiple letter, or even an underscore or a numeral. Spaces, punctuation mark and other symbols are not regarded as variables. Variable identifiers are significant in C++, as they distinguish one variable from the others. We should also be careful while using upper or lower case. You can name the identifier using any word. However, the following set of words is restricted in C++:

```
asm, auto, bool, break, case, catch, char, class,
const, const_cast, continue, default, delete, do,
double, dynamic_cast, else, enum, explicit, export,
extern, false, float, for, friend, goto, if, inline,
int, long, mutable, namespace, new, operator, private,
protected, public, register, reinterpret_cast,
```