

```

    cout << "The minimum short integer is: " <<
SHRT_MIN << "\n";
    cout << "The maximum short integer is: " <<
SHRT_MAX << "\n\n";
    return 0;
}

```

The output of this program will be:

```

The minimum signed character: -128
The maximum signed character: 127
The minimum short integer is: -32768
The maximum short integer is: 32767

```

The constants defined in the `climits/limits` library are as follows:

```

CHAR_BIT  INT_MAX  LONG_MAX  SCHAR_MAX  SHRT_MAX
CHAR_MAX  INT_MIN  LONG_MIN  SCHAR_MIN  SHRT_MIN
CHAR_MIN  UINT_MAX  ULONG_MAX  UCHAR_MAX  USHRT_MAX
                                     MB_LEN_MAX

```

In the `cfloat` library, we can get some double precision numbers provided by C++. These are as follows:

```

DBL_DIG      FLT_DIG      LDBL_DIG
DBL_EPSILON  FLT_EPSILON  LDBL_EPSILON
DBL_MANT_DIG  FLT_MANT_DIG  LDBL_MANT_DIG
DBL_MAX      FLT_MAX      LDBL_MAX
DBL_MAX_10_EXP  FLT_MAX_10_EXP  LDBL_MAX_10_EXP
DBL_MAX_EXP  FLT_MAX_EXP  LDBL_MAX_EXP
DBL_MIN      FLT_MIN      LDBL_MIN
DBL_MIN_10_EXP  FLT_MIN_10_EXP  LDBL_MIN_10_EXP
DBL_MIN_EXP  FLT_MIN_EXP  LDBL_MIN_EXP
FLT_RADIX

```

There is also a constant, called `NULL`. We can use this constant to assign a task, to which the pointer will not hold a valid value. The definition of the `NULL` constant is available in the `cstddef` library.