

>>

SHR

Shift Right

● Explicit type casting operator:

We can convert the datum of a given type to another type by using the Explicit type casting operator that accepts a single parameter. This parameter can be either a type or another variable. `sizeof()` is regarded as an Explicit type casting operator.

Example:

```
x = sizeof (char);
```

● Precedence of operators:

While writing a complex expression involving multiple operands, we may encounter difficulties in deciding the sequence of operands in the preferred order.

Let us look at the priority order from greatest to lowest:

Operator	Description	Grouping
::	scope	Left-to-right
() [] . -> ++ -- dynamic_cast static_cast reinterpret_cast		
const cast typeid	postfix	Left-to-right
++ -- ~ ! sizeof new delete	unary (prefix)	Right-to-left
* &	indirection and reference	Right-to-left
+ -	unary sign operator	Right-to-left
(type)	type casting	Right-to-left
.* ->*	pointer-to-member	Left-to-right
* / %	multiplicative	Left-to-right
+ -	additive	Left-to-right
<< >>	shift	Left-to-right
< > <= >=	relational	Left-to-right
== !=	equality	Left-to-right
&	bitwise AND	Left-to-right
^	bitwise XOR	Left-to-right
	bitwise OR	Left-to-right
&&	logical AND	Left-to-right