

Here, we have three integer variables - *a*, *b* and *c*, where the three numbers are stored. Initially, the code checks whether '*a*' is greater than '*b*' or not. If '*a*' is greater, then it checks whether '*a*' is greater '*c*' or not. If this condition is true, then the greatest number will be the value of '*a*'. Otherwise, the greatest number will be the value of '*c*'. If the first '*if*' condition returns false, then it checks whether '*b*' is greater than '*c*' or not, with the help of another '*if*' statement.

If this condition is true, then the greatest number will be the value of '*b*'. Otherwise, the greatest number will be the value of '*c*'. You can combine multiple conditions in a single '*if*' statement with the help of logical operators such as '&&' and '||'. Using this concept the previous code can be written as follows:

```
if(a>b && a>b)
    cout<<"The greatest number ="<<a;
if(b>a && b>c)
    cout<<"The greatest number ="<<b;
if(c>a && c>b)
    cout<<"The greatest number ="<<c;
```

Program 1:

The following program will accept any year i.e. an integer value from the user, and checks whether the year is a leap year or not. Go through the program and its explanation carefully.

```
#include<iostream.h>
int main()
{
    int year;
    cout<<"Please enter any year of your choice=">";
    cin>>year;
    if(year%100==0)
    {
        if(year%400==0)
            cout<<"You have entered "<<year<<" and this is
```