

```
int main ()
{
    int x=5, y=3, v;
    v = sub(7,2);
    cout << "The first result is " << v << '\n';
    cout << "The second result is " << sub(7,2) <<
'\n';
    cout << "The third result is " << sub(x,y) <<
'\n';
    v= 4 + sub(x,y);
    cout << "The fourth result is " <<v << '\n';
    return 0;
}
```

The output of this program is:

```
The first result is 5
The second result is 5
The third result is 2
The fourth result is 6
```

Here, within the `main()` function, a variable `v` of the type `int` is declared. Another two variables `x` and `y` are declared and initialised with values 5 and 3, respectively. In the next line, the function `sub` is called by the variable `v`. Two values, 7 and 2, are passed to this function. Then the function `sub` is executed. The values 7 and 2 is assigned to the local variables `m` and `n`, respectively, and the result of subtraction is stored in another local variable `k`. Hence, the value of `k` will be 5. The function `sub` returns the value of `k`. This return value is stored in the variable `v` used to call the function `sub`. Next, `cout` displays the value of `v`. Next, the function `sub` is again called by the same values. However, this time the return value will be displayed directly by `cout` without assigning it to any variable. After that the function `sub` is again called, but this time two variables mentioned above are passed to it. So the function `sub` will be executed with the values of the variables `x`