

Cookies can also be set in array as given below:

```
<?php
setcookie("owncookie[a]", "First Cookie");
setcookie("owncookie[b]", "Second Cookie");
setcookie("owncookie[c]", "Third Cookie");
if (isset($_COOKIE['owncookie'])) {
    foreach ($_COOKIE['owncookie'] as $cookieName =>
$Ourcookie) {
        echo "$cookieName : $Ourcookie <br />\n";
    }
}
?>
```

`print_r($_COOKIE)`; can be used to display all the available cookies

9.2. Deleting a cookie

For deleting a cookie, `setcookie()` is called with the name argument like `setcookie("Ourcookie")`. However, this argument does not work always. Hence, it is advised to set the cookie with an already expired date. Look at the delete example below:

Example:

```
<?php
setcookie("Ourcookie ", "", time()-3600);
?>
```

9.3. Creating session cookie

For creating a cookie that is valid till the user runs his/her browser, you can pass `setcookie()` with an expiry argument of 0. In such a case, your browser continues to run and cookies are returned to the server. Once the browser quits and restarts, it does not remember them.

This is useful for the scripts validating a user with a cookie. This also enables you to have regular access to personal information on different pages, once the password is submitted.

See the syntax below:

```
setcookie( "session_id" , "66343" , 0 ) ;
```