

```
<?php
    session_start(); // It connects to the existing
    session or starts a new session
    session_register ("id"); // It creates a session
    variable called id
    session_register ("prod"); // It creates a ses-
    sion variable called prod
    $HTTP_SESSION_VARS ["id"] = $id; // It sets value
    of id by variable $id
    $HTTP_SESSION_VARS ["prod"] = $prod; // It sets
    value of job by variable $prod
?>
```

The code mentioned above first connects to the session that is already present. It now creates two session variables with values set from the HTML form. As a PHP variable is added to a session file, it uses `session_register()` function. Only the variable name is written and the code appears `$HTTP_SESSION_VARS("id") = $id` is used.

When PHP variables are referred in a session file, the dollar (\$) sign is not used. It is only used when the variables are used in the script. Once a session variable is registered, it is used like a normal PHP variable. A script with an updated session variable does not require an updated session file. Session management automatically does this with the end of the script. Therefore the script would appear as:

```
$name = "myname";
```

The new value is automatically written to the session file. To create a new session variable, the following code can be used:

```
session_register ("variable_name");
$variable_name = "newvar";
```

The above mentioned variable is available to all PHP pages connecting to the session that uses `session_start()`. Since the values of the form variables are stored, any PHP page that connects to the session, can read the variables.

To destroy a session file, use the following function:

```
session_destroy();
```