

10.3. E-mail

With PHP you can send e-mails directly from a script. With `mail()`, the messages are automatically mailed to the specified receiver. Similar mails can be forwarded to multiple recipients by putting a comma in the 'to' column between the addresses. This function can be applied to send some special content types as well as emails with attachments.

This function takes receiver(s) email-id, subject, content of mail, additional headers like Cc, Bcc, etc. and additional parameters as arguments. The last two arguments are optional.

On successful delivery of the mail, `mail()` returns TRUE, otherwise a FALSE value is returned.

Example:

```
<?php
mail("abc@ourmail.com", "urgent", "Hello\nHow are
you");
?>
```

To pass a fourth string argument, you can insert it at the end of the header. You can also add extra headers by using this function. Multiple headers can also be added. Here we need to use a carriage return and a new line to separate each header from the other. While sending the mails we must separate the headers using `\r\n`.

Following code can be used to send mail with extra headers:

```
<?php
$receiver = "myfriend@ourmail.co.in";
$subject = "wish";
$content = "Hi! My dear friend how are you.";
$sender = "myself@ ourmail.co.in ";
$headers = "From: $sender";
mail($receiver,$subject, $content,$headers);
echo "Mail has been sent successfully.";
?>
```

To send mail with extra headers and additional command line parameter use the code below:

```
<?php
mail("myfriend@ourmail.co.in ", "$subject", $con-
tent,
```