

The above code is not secure, as even an unauthorised user can insert data into the mail headers through the input form. Suppose the user adds the text given below into the email input field within a form:

```
myfriend@ourmail.co.in%0ACc:newfriend1@    our-
mail.co.in
%0ABcc:  newfriend2@ourmail.co.in,  newfriend3@
ourmail.co.in,
  a n o t h e r f r i e n d 1 @ o u r m a i l . c o . i n ,
anotherfriend2@ourmail.co.in
%0ABTo:anotherfriend3@ourmail.co.in
```

The above text is put into the mail headers by the mail() function. Now the new header comprises of extra Cc:, Bcc:, and To: field. As the user clicks on the submit button, the email is sent to the supposed addresses.

The following is a piece of code which checks whether the email address that was provided is a valid email address or not:

```
<html>
<body>
<?php
function mailcheck($check_mail)
{
    $check_mail = filter_var($check_mail, FILTER_SANITIZE_EMAIL);
    if ( filter_var ( $ c h e c k _ m a i l ,
FILTER_VALIDATE_EMAIL) )
    {
        return TRUE;
    }
    else
    {
        return FALSE;
    }
}
if (isset($_REQUEST['mail']))
    $validate_mail = mailcheck($_REQUEST['mail']);
if ($validate_mail ==FALSE)
{
```