

There are certain databases which are supported by PHP through protocol-based functions. These include:

- ODBC
- LDAP
- DBM style

Let us discuss about each of these databases in detail:

Informix: the Informix driver is employed for Informix (IDS) 7.x, SE 7.x, Universal Server (IUS) 9.x and IDS 2000 in “ifx.ec” and “php_informix.h” in the informix extension directory. IDS 7.x support is finished with a good support for BYTE and TEXT columns. IUS 9.x support is not completed fully. Here we have some new data types except SLOB and CLOB as these supports are not yet completed.

DBM (Berkeley): DBM functions provide certain high performance implementations and source codes relevance, for different interface applications. Apart from this, they cannot be used for any other functions. The DBM applications can be compiled by replacing the application’s #include of the DBM or NDBM include file. The lines mentioned below focus on this concept:

```
#define DB_DBM_HSEARCH 1
#include <db.h>
```

‘dbm datum typedef’ basically describes two objects including key and content. A dbm data focuses on a series of dsize bytes presented by the dptr. It also includes binary data as well as text strings. A dbm database can be opened by the dbmopen function. This helps in opening and creating a database file.db. The open database can be closed by calling dbmclose.

MSSQL (Microsoft): PHP uses MySQL server in a stack of software such as LAMP or WAMP stacks. In some occasions, PHP uses MSSQL databases in the back-end. With the PHP scripts certain web applications are also made, exposing the MSSQL Databases. The MSSQL, a relational database management system, was produced by Microsoft. MS-SQL and T-SQL are the two query languages of MSSQL.

Sybase: Sybase provides a detail introduction about Sybase SQL Server. It also offers the system model and some tools and components of the Sybase System 11. It is a client server database engine.