

```
print_r($array_learning);

// Re-index:
$array_learning = array_values($array_learning);
$array_learning[] = 70;
print_r($array_learning);
?>
```

The output of this program is as follows:

```
Array ( [0] => 10 [1] => 20 [2] => 30 [3] => 40 [4] => 50 ) Array ( ) Array
( [5] => 60 ) Array ( [0] => 60 [1] => 70 )
```

3.2 Multidimensional arrays

Multidimensional Arrays are the most complex arrays in PHP. As the name suggests, these are data structures that hold various other arrays. Various arrays are used as sub-array elements in a Multidimensional Array. We can easily identify the difference between a single dimensional array and a multidimensional array. In a single dimensional array, we set a value for a single key and assign a number of values to several keys. For example, we may assign values like 'class', 'section', 'roll number' to a single dimensional array that contains information on 'Student'. On the other hand, a multidimensional array 'Student' may include the break up like, 'Personal data' 'Marks', 'Attendance,' etc. Each of these sections is a single dimensional array that is treated as a separate array.

Look at the example below:

Example 1:

Here we have created a 'Multidimensional Array' by using the automatically assigned ID keys:

```
$relatives = array
(
    "Robin"=>array
    (
        "Ram",
        "Bharat",
        "Adam"
    ),

```