

to mark the end of the variable.

Example:

```
<?php
$fruit = 'mango';
echo "$fruit 's taste is good <br>";
echo "He eat some $fruits <br>";
echo "He eat some ${fruit}s <br>";
echo "He eat some {$fruit}s <br>";
?>
```

The output of the above program is:

```
mango's taste is good
He eat some
He eat some mangos
He eat some mangos
```

In the above example, a variable `$fruit` is assigned with a string `'mango'`. Then its value is displayed using different methods. In the first statement, `" "` is an invalid character for a variable. Therefore, it is treated as a symbol (`'`). In the second statement, `"s"` is a valid name, so `'$fruits'` is treated as a variable where no value is assigned. The other two statements show how variable names can be enclosed within braces.

In the same way, you can insert an array index as well as an object property that is to be parsed. The square bracket indicates the closing of the index.

You can declare an array as:

```
$shirt = array('tshirt' => 'white', 'bushshirt'
=> 'black');
```

Then the statements given below will execute properly:

```
echo "Tshirt is $shirt[tshirt].";
echo "Tshirt is $shirt[tshirt].";
echo "Tshirt is {$shirt['tshirt']}. ";
echo "Tshirt is " . $shirt['tshirt'] . " .";
```

All the statements mentioned above will give the same output:
Tshirt is white.