

automatically provides the description of the PHP global variables related to the server and client environments. Hence, these variables are called environment variables. The variables in PHP vary depending on system, server and configuration. See the examples of environment variables in the following table:

Example:

Name of the variable	Description	Example
<code>\$HTTP_USER_AGENT</code>	Client's Name and version	Mozilla
<code>\$REMOTE_ADDR</code>	The IP address of the client	155.148.65.33
<code>\$REQUEST_METHOD</code>	Whether the request was GET or POST	POST/GET
<code>\$QUERY_STRING</code>	For GET requests, the encoded data send appended to the URL	<code>id=I001t&product=abcd</code>
<code>\$REQUEST_URI</code>	The full address of the request including query string	<code>/php-learning/book/unit_07/newpage.html?id=I001</code>
<code>\$HTTP_REFERER</code>	The address of the page from which the request was made	<code>http://www.ourpage.com/newpage.html</code>

Apart from header-oriented variables, PHP also offers certain other global variables. You can directly access this variable as the global variable `$PHP_SELF`. You can also use it as a string in the HTML forms action argument. This saves time in hard coding the page name. Both the global and environmental arrays in PHP are useful in different ways.

7.2. Script to accept user input:

The HTML form can be separated from PHP code. See the example below:

Example:

```
<html>
<head>
```