

Note that by default, Linux does not make two copies of the same file when it is compressed or uncompressed. That means that if the above command is executed, the folder will have a `LiVES-0.9.9.5.tar` file, but the `LiVES-0.9.9.5.tar.gz` file will be deleted.

To unpack a `bz2` file, type in
`$bunzip2 file.bz2`

To unzip a `.zip` file, type in
`$unzip file.zip`

These commands will unpack the contents into a separate folder with the file name, after subtracting the extensions.

To make a compressed archive out of a directory, type
`$tar -c directory/ | bzip2 > directory.tar.bz2`

Sundry commands

To see a list of all available commands:

Go to the command line

press `[Tab]` twice. Beware though, on complex systems, you will get a prompt like:

Display all 3171 possibilities? (y or n)

If you are going to type `y`, it is a good idea to go to `edit>pro-file preferences>scrolling` and change the scrollbar to 5000 lines or more. Note, the filesize increases, 5000 lines are worth 3.1 MB.

A variation of this command is typing some text and then pressing `[Tab]` twice, which shows all the commands that start with those letters.

For example,

`$ su[Tab][Tab]`

Which gets the output

<code>su</code>	<code>sudoedit</code>	<code>sum</code>	<code>su-to-root</code>
<code>sudo</code>	<code>sulogin</code>	<code>suspend</code>	

To find out all variations of a command, type in

`$man ls`

which gives an output like:

NAME