

The command line appear as follows:

```
Preparing...##### [100%]  
1:packagename##### [100%]
```

This means that the package has been installed properly.

Another easy way to install is to use the apt-get command for debian-based distributions. In the command line, type:

```
$ sudo apt-get install packagename
```

So, for example, if you want to install a game called pingus, type:

```
$ sudo apt-get install pingus
```

The response should appear as follows:

```
Reading package lists... Done Building dependency  
tree Reading state information... Done The following  
extra packages will be installed: libboost-sig-  
nals1.34.1 libsdl-image1.2 libsdl-mixer1.2 pingus-  
data The following NEW packages will be installed:  
libboost-signals1.34.1 libsdl-image1.2 libsdl-  
mixer1.2 pingus pingus-data 0 upgraded, 5 newly  
installed, 0 to remove and 212 not upgraded. Need to  
get 12.4MB of archives. After this operation, 23.9MB  
of additional disk space will be used. Do you want  
to continue [Y/N]?
```

Notice that the dependencies are being resolved in the command line. Type in Y and press [Enter]. The command line will show a list of packages and how much time is left.

```
7% [4 pingus-data 763299/11.3MB 6%]  
43.6kB/s 4min21s
```

Assuming you have yum installed, the apt-get equivalent for SuSE is

`$ yum install packagename`. If you do not, then please install it as handling the dependencies will be troublesome otherwise.

To make sure that the apt-get command is working at all times, make sure that the repositories on the system are always updated. To do this, in the command line type:

```
$ sudo apt-get update
```

Note: If the programs don't appear in the menu after installation for any of the other methods, the programs will be located in one of the two bin folders on your file system. This is either `/usr/bin`, or `/usr/local/bin`.