

which will show the suggestions, in our case that would be the `<div>` with the id "suggestions". The third parameter is the name of the dataset from which to get the results. The fourth parameter is the column of the dataset in which to search.

The final parameter is a list of options, which control the functioning of the feature. Here the options we set are:

- **minCharType**: This controls how any characters need to be entered before the autosuggest starts looking for matches. Here we set it to 0, to make it always search.
- **containsString**: This setting allows us to optionally search the whole text, instead of just the first few characters.
- **maxListItems**: This controls how many items are displayed in the list. To list all items we set it to '0'.

That is all the code that is required in JavaScript! You must be thinking, "But we didn't do anything!" You're right Spry takes care of it all. All we need to do is where to put the data, and how to put it there.

How do we tell Spry where to put the data? Let's see.

```
<table width="500" border="0" cellpadding="0"
cellspacing="0"
```

```
  spry:region="moviesPage">
```

```
    <tr>
```

```
      <th scope="col" onclick="moviesPage.
sort('rank')">Rank</th>
```

```
      <th scope="col" onclick="moviesPage.
sort('name')">Name</th>
```

```
      <th scope="col" onclick="moviesPage.
sort('earning')">Earning</th>
    </tr>
```

```
  <tr spry:repeat="moviesPage">
```

```
    <td>{rank}</td>
```

```
    <td>{name}</td>
```

```
    <td>{earning}</td>
```

```
  </tr>
```

```
</table>
```