

CSS is very powerful in describing the style of documents, and defining complicated rules for the style that should be applied to a particular element and under what conditions. For example, if we wanted all links to be bold and green under normal conditions, and red and underlined when the mouse is hovered over it, the code would be as follows:

```
<style>
  <!--

  a {
    color: #00ff00;
    font-weight: bold;
  }

  a:hover {
    color: #ff0000;
    text-decoration: underline;
  }
  -->
</style>
```

This would be placed inside the document header.

Basically, all styles are placed within a `<style>` tag, enclosed within the comment tag `<!-- -->`. They can also be placed in a CSS file, and included within the HTML page. To include a CSS file or stylesheet (known as `my_style.css`) in an HTML file, we use the `<link>` tag in the header of the document. The syntax to do so is:

```
<link rel="stylesheet" type="text/css"
href="my_style.css"/>
```

In CSS, to define any sort of style, you need to have two things ready. First, what all elements it should apply to, i.e. the scope of the style, also known as the selector. Second, you need to provide what styles you want to apply to it. This is similar to the situation where you need to assign a particular value to a variable. Here, you need the name of the variable as well as the value you want to assign.

However, unlike a case of assigning a value to a variable, we are applying a set of styles to a group of elements. This is a group assignment rather than a one-to-one correlation.