

Every time you click, a new numbered entry called 'Series #' will be added, where # is the series no.

Let's see how this is done.

Now, what we added was a new variable called 'len', which will store the current no of items in the list. How it does that is, it retrieves the 'sermovies' list element, from which it retrieves an array all the tag elements, and assigns the length of that to 'len'. So 'len' basically has the number of entries in the list. Now we increment 'len' to get the next entry's number. This is now added in front of the new entry, which is then appended to the list.

The end result — every time you click on the heading, a new series keeps getting added to the list. They will come numbered as 'Series 4', 'Series 5' and 'Series 6'. The reason they start from 4 is that 3 items are already there in the list, 'The Matrix Series', 'The Lord of the Rings Series' and 'Star Wars Series'.

Surely, this is more dynamic than before, but still, it is essentially useless! Let us now make it more interactive by allowing a user to enter the name of the movie series to be added.

For this we will need to add some content to the HTML page, some kind of form where they can enter a movie name. Let us place a text input box under the movie series list for the purpose, and add a button to add a name to the list. Here is the final HTML code for that:

```
<html>
  <head>
    <title>My Favorite Movies</title>
    <script language="JavaScript">
      <!--
        function addmovie(){
          movieName = document.getElementById(
            'newseries').value;
          document.getElementById('newseries').value =
            '';
          document.getElementById('sermovies').
            innerHTML += '<li><a href=".">'
            + movieName +
            '</a></li>';
```