

```

    }
    -->
</script>
</head>
<body>
    <h1>A List of my favorite Movies</h1>
    <h2>Movie Series:</h2>
    <ul id="sermovies">
        <li><a href=".">The Matrix Series</a></
li>
        <li><a href=".">The Lord of the Rings
Series</a></li>
        <li><a href=".">Star Wars Series</a></
li>
    </ul>
    <input id="newseries" type="text" /><input
type="button" onclick="addmovie()" value="Add
Series" />
    <h2>Individual Movies:</h2>
    <ul id="indmovies">
        <li><a href=".">Memento</a></li>
        <li><a href=".">Batman Begins</a></li>
        <li><a href=".">The Dark Knight</a></li>
        <li><a href=".">Gattaca</a></li>
        <li><a href=".">Shawshank Redemption</
a></li>
    </ul>
</body>
</html>

```

Now let's see what we've done here. First, we've added two new `<input>` tags below the first list. One is of type 'text', and the other 'button'.

The `<input>` tag of type 'text' is a text input box, where the user may type the name of the movie. It has been given an ID of 'newseries', so that its value can easily be used in JavaScript later on.

The `<input>` tag of type 'button' is well, a button! It has an 'onclick' property set to 'addmovie()', so that when the user clicks on the button, the 'addmovie' function is called. It also