

has an attribute 'value', set to 'Add Series', this is the label that will appear on the button.

The addmovie function itself has been modified to accommodate this change. The changes made to the function are:

- A new variable called 'movieName' is now added and set to the value of the textbox with an 'id' of 'newseries', in the line: `movieName = document.getElementById('newseries').value;`
- The value of the textbox is being cleared by setting it to an empty string. This way the user can start typing a new name immediately. We do this using: `document.getElementById('newseries').value = '';`
- The value being set for each new entry to the list is set to the value entered in the textbox. This is done by modifying the old code which would just add a number after the string 'Series' to: `document.getElementById('sermovies').innerHTML += '<li><a href=".">' + movieName + '</a></li>';`
- The old code to calculate the number of items in the list has been removed.

If you run it now you will see that the value you enter in the textbox is added to the list when you click the button.

Now let's play around a little more. We will now add another set of textbox and button to enter movies in the individual movies list.

Also the function 'addmovie' is too restricted, as it will only add movies to the 'Movie Series' list. We will now give it some parameters so that it can work with both cases, and in fact can be used any any new list we might add.

Here is the new proposed function:

```
<script language="JavaScript">
<!--
        function addmovie(nameid, listid){
            movieName = document.getElementById(nameid).
value;
            document.getElementById(nameid).value = '';
            document.getElementById(listid).innerHTML +=
'<li><a href=".">'
            + movieName + '</a></li>';
        }
```