

```

        <earning>431088295</earning>
    </movie>
</movie>
        <rank>4</rank>
        <name>E.T. THE EXTRA-TERRESTRIAL
(1982)</name>
        <earning>399804539</earning>
    </movie>
</movies>

```

The code seems complicated doesn't it? To make it simpler let's focus on what needed to be done and how it was done.

First, we need to load the external XML document containing the data. In this case, we make the data load when the page loads, using the 'onload' event of the <body> tag. To load the data, we first need to create an XMLHttpRequest object, which we create using the 'createAjaxObject' function described earlier. To actually use the object, we need to do the following:

- We need to provide a function that will be called when the data finishes loading, or fails to load. We do this by setting the 'onreadystatechange' property of the XMLHttpRequest object to a function which will handle the data, or error in loading.
- We need to supply the target file to load, and the mode in which it is to be loaded. This is done by calling the 'open' function of the XMLHttpRequest object. The function takes three parameters. The first is the mode, usually this will be 'GET', to retrieve data from a location. The second parameter specifies the path of the file to be loaded, in this case 'movies.xml', as the file is in the same directory as the HTML file. The final parameter is specifies whether we wish to load the data asynchronously. Loading synchronously means that the execution of the code will stop till the entire document located at the remote site has downloaded, and with asynchronous loading, the data will load in the back while the file continues executing. We wish to use it asynchronously, so we set it to true.
- Finally, we inject this data into our page as done in the 'onDataLoad' function.