

The 'onDataLoad' function deserves an explanation owing to its complexity. Let us look at it step by step:

- `if (dataLoader.readyState != 4)`
`return;`

This code is responsible for checking if the data has finished loading. A ready state of 4 indicates that the request is complete.

- `if (dataLoader.status != 200 && dataLoader.status != 0)`
`return;`

This code checks whether the data loaded successfully. A status of 200 means that the data was loaded successfully. However status messages are not sent when loading a local file, such as we are using, and the example can fail to work, so we need to add a check for a status of '0' too. The statement inside the brackets after 'if' is a check for status NOT equal to '200' AND status NOT equal to 0. That is to say it should be neither '200' nor '0', or else the function will 'return' without doing anything.

- `data = dataLoader.responseXML.documentElement.getElementsByTagName('movie');`

Here we assign the list of movie elements in the loaded document to a variable called 'data'.

- `movietable = document.getElementById('movies');`

Here we assign a reference to the table containing the movie list to movietable, so that it may be conveniently used, or called.

- `for (i = 0; i < data.length; i++) {`

This loop will run for all the items in the XML data source.

- `newrow = movietable.insertRow(-1);`

This will add a new row into the movie table, and put a reference to the newly created row in the variable 'newrow'.

- `newrow.insertCell(-1).innerHTML = data[i].getElementsByTagName('rank')[0].textContent;`
`newrow.insertCell(-1).innerHTML = data[i].getElementsByTagName('name')[0].textContent;`
`newrow.insertCell(-1).innerHTML = data[i].get`