

`ElementsByTagName('earning')[0].textContent;`
 These three lines add the values for the three columns. They work in the same manner, so let us look at only the first. Here `'data[i]'` refers to the *i*-th element of data in the data source. The `getElementsByTagName` function is used on the *i*-th data element, to retrieve a list of elements in that node which are of the type `'rank'`. Since there will be only one, we use the 0-th element, which will give us the node containing the rank of the movie. We then retrieve the contents of the tag, which is then assigned to a newly inserted cell in the table using the `innerHTML` property.

Now that you've been introduced to the developer side of things, let's look behind the scenes. How does this application flow?

- The browser loads the main HTML page
- The browser calls the JavaScript function `'loadData'`
- The browser sends a request to load `'movies.xml'`
- The browser calls the function `'onDataLoad'` every time the status of its request for `movies.xml` changes, i.e. when the request is initiated, when the request is sent, when it is processed, and finally when the request is complete.
- When the status becomes `'4'`, implying that the request is complete and loaded, the browser starts executing the rest of the `'onDataLoad'` function.
- The `'onDataLoad'` function iterates over each data entry from the XML file and adds them to the page in the table.

That should cover it. We hope you've grasped the concept of what is going on in this example. If you are in doubt, go through it again, it will greatly help in understanding what's to come.

5.3 Further down the AJAX road

In this section, we will continue with the AJAX application we created above, and continually improve on it, making it into a true database.

The application we constructed before was a fair example, but it's quite static. Looking at it, one cannot discern it from a