

```

tElement.getElementsByTagName('movie');
    movieTable = document.getElementById('movies');
    dataLength = data.length;
    noOfPages = data.length / itemsPerPage;
    displayPage(0);

```

The function is quite simple; the only new thing it does is set 'dataLength' to the number of items in the XML database. It also calculates the number of pages of data by dividing the number of items of data by the items to be shown on each page. It calls the 'displayPage' function with a parameter of '0', basically telling it to display the first page.

The 'displayPage' function is just a modified second-half of the original 'onDataLoad' function. Instead of displaying the whole list, it calculates the starting and ending positions of the items on the supplied page number, and displays only those.

Another thing required of this function is to clear out old data. We do that by repetitively deleting the second row of the table (index 1) till there is only one row left, which is the header. As you may have guessed this is done using the while loop in the code example. It keeps deleting the second row ('movieTable.deleteRow(1)') as long as the no. of rows ('movieTable.rows.length') is more than one.

```

function displayPage(pagenum){

    startItem = pagenum*itemsPerPage;
    endItem = startItem + itemsPerPage;

    while( movieTable.rows.length >1 )
        movieTable.deleteRow(1);

    for (i = startItem; i < endItem; i++) {
        newrow = movieTable.insertRow(-1);
        newrow.insertCell(-1).innerHTML =
data[i].getElementsByTagName('rank')[0].textContent;
        newrow.insertCell(-1).innerHTML =
data[i].getElementsByTagName('name')[0].textContent;
    }
}

```