

Menu’.

- `for (i=0; i<noOfPages;i++)`
Quite clearly, this will repeat the loop for each page.
- `newcell = navMenu.insertCell(-1);`
This creates a new cell at the end of the row (index -1), and stores a reference to it in the variable ‘newcell’.
- `newcell.innerHTML = i+1;`
Now we add the page number inside the cell. The page number will be one more than the index, because while computers work with a starting index of 0, for humans (who will be using the page), 1 is a more comfortable place to start.
- `newcell.onclick = new Function("displayPage(" + i + ");");`

This line does the equivalent of setting the ‘onclick’ attribute of the table cell to ‘displayPage(i)’. Let us look at the HTML equivalent of this when ‘i = 3’, for better clarity:

```
<td onclick='displayPage(3)'+4</td>
```

The code element ‘new Function()’ creates a function which has the code that is provided in the parameter.

Take a look at the complete code of our application as of now. The script part and the HTML part are shown separately, as the code is quite large.

Script part:

```
var dataLoader;
var data;
var dataLength = 0;
var itemsPerPage = 10;
var noOfPages = 0;
var movieTable;

function createAJAXObject(){
    var httpReq;
    try {
        httpReq = new XMLHttpRequest();
    }
    catch (e) {
        try {
            httpReq = new ActiveXObject("Msxml2.
```