

```

textContent;
    }
}
function gotoPage(direction){
    newpage = currentPage + direction;
    if(newpage < noOfPages && newpage >= 0)
        displayPage(newpage);
}

```

In the updated 'displayPage' function, we now check if the page requested is '-1' or the last page, in which case, we go to the last page (the last page will be one less than the noOfPages, as the no of pages counts the 0th page as well). It also updates the global 'currentPage' variable with the current page number. Not that the variable 'currentPage' has to be declared once outside all the functions to be accessible globally.

In the new 'gotoPage' function, we first calculate the new page number, by adding 'direction' to the current page (newpage = currentPage + direction). Then we check if the new page number is within bounds, or basically that it is less than the total number of pages (newpage < noOfPages) and not less than zero (newpage >= 0). If the new page number is within bounds, we go directly to it (displayPage(newpage)).

Now take a look at the HTML code for the new navigation mechanism.

```

<table border="1">
  <tr>
    <td onclick="displayPage(0)">first</td>
    <td onclick="gotoPage(-1)">previous</td>
    <td onclick="gotoPage(1)">next</td>
    <td onclick="displayPage(-1)">last</td>
  </tr>
</table>

```

This can be placed between the data list, and the pages list. Before we take a look at the code as a whole, let us first add another feature quite popular in web sites. That is to let the user select how many items to show on the page. This can be done by giving the user a combo box / dropdown box containing a number of options. For our purposes, we will give the