

```

        for (i = 0; i < dataLength; i++) {
            if (data[i].textContent.
indexOf(searchtext) > -1) {
                newrow = document.getElementById('suggestions').insertRow(-1);

                newrow.insertCell(-
1).innerHTML = data[i].getElementsByName('rank')[0].textContent.replace(searchtext, "<span
class='match'>" + searchText + "</span>");

                newrow.insertCell(-
1).innerHTML = data[i].getElementsByName('name')[0].textContent.replace(searchtext, "<span
class='match'>" + searchText + "</span>");

                newrow.insertCell(-1).innerHT-
ML = data[i].getElementsByName('earning')
[0].textContent.replace(searchtext, "<span
class='match'>" + searchText + "</span>");
            }
            if (document.getElementById('sugges-
tions').rows.length > noOfSuggestions)

```

Now this looks REALLY complicated! But let's look only at the changes in the code. That would be the right-hand side of the three (`newrow.insertCell(-1).innerHTML =`) lines. Let's see what one of them does, and the others follow the same principle.

Instead of the original:

```
newrow.insertCell(-1).innerHTML = data[i].
getElementsByName('name')[0].textContent;
```

We now have:

```

newrow.insertCell(-1).innerHTML =
data[i].getElementsByName('name')[0].
textContent.replace(
    searchText,
    "<span class='match'>"
    + searchText +
    "</span>"
);

```