

your hard disk. Also, if you ever want to install/uninstall more packages, just run the setup again keeping the install location same and you can modify your selection any number of times.

Proceeding slowly about it, let us first compile a simple “Hello World” application written in C++.

First, open your favourite text editor and type in the following statements exactly and save the file as “filename.cpp”

```
#include<iostream>
int main()
{
    std::
cout<<“FastTrack to
OpenSource”;
    return 0;
}
```

Now open your shell (either the native Linux shell or the cygwin command prompt) and by using the **cd** command change to the directory where you have stored your “filename.cpp”

Issue the following command

```
g++ filename.cpp
```

Now issue

```
./a.out
```

You have just written, compiled and executed your first application.

As the applications get more features and increase in complexity, they start having more than one source file and various other libraries that need to be packaged together for successful compilation and installation. For this very reason most open source distributions use the “GNU build system” or



For Linux users, the commands mentioned below in this tutorial need to be entered in the console, which can be opened in any of the following ways

1) Press

```
[Alt]+[Ctrl]+[F2]/
[F3]/[F4]/[F5]/[F6]
```

2) If you are in KDE, type Console in your application environment

3) If you are in Gnome, you can use the “Gnome-Terminal” application

So now we are ready to compile our first program. If you have installed cygwin with all the devel packages as mentioned above you are ready to go. For Linux users most distributions will come by default with the basic build tools, but if not you can install the build-essential package from your package manager or via command line. For example in debian based distributions, the following should do the trick

```
sudo apt-get install
build-essentials
```