

Received Signal Strength Indicator (RSSI) was added.

Bluetooth 1.2 was backward compatible with 1.1. Backward compatibility means that anything that worked on Bluetooth 1.1 would definitely work on 1.2 although the reverse need not be the case.

The major improvements were:

- Faster connection and discovery
- Adaptive frequency hopping spread spectrum (explained earlier: how a signal is transmitted across various frequencies for better noise reduction and interference)
- Better transmission speeds
- Improved voice quality
- Checked and ratified as IEEE Standard 802.15.1-2005

Bluetooth 2.0 was released on November 10, 2004.

Backward compatibility was ensured and the main change

Backward compatibility with earlier versions ensures older Bluetooth devices will continue to function with newer devices

was faster data transfer by introduction of an enhanced data rate. Using a combination of various different radio technologies, Gaussian frequency shift keying (GFSK) and phase shifting keying (PSK), it managed to improve the data rate. The 2.0

specification allows for benefits such as more than three times the transmission speed, reduced complexity in case of multiple simultaneous connections, and lower power consumption. The EDR is an optional feature.

Bluetooth 2.1 was released on July 26, 2007 and the following features were added. In non-technical terminology, the benefits were:

- Better filtering of devices before connection using a more sophisticated method of collecting information about the device, its manufacturer and other details.
- Lower power consumption when not engaged in active transmission and waiting and searching for nearby Bluetooth devices. This specially benefits wireless keyboard and mouse devices as it increases their battery life by letting