

3 Desktop and Applications

Quick Tip

Do not randomly enable or disable services from the desktop. Doing so can prevent an OpenSolaris system from booting.

```
$ svcs -a | grep nwam
online          Jan_14    svc:/network/
physical:nwam

If you want to list out all the services which are
currently enabled, then run the following command:
$ svcs -a | grep online | less
online          Jan_14    svc:/system/svc/
restarter:default
online          Jan_14    svc:/network/loopback:default
online          Jan_14    svc:/network/datalink-
management:default
online          Jan_14    svc:/system/identity:node
online          Jan_14    svc:/system/metainit:default
online          Jan_14    svc:/system/filesystem/
root:default
online          Jan_14    svc:/system/scheduler:default
online          Jan_14    svc:/system/cryptosvc:default
online          Jan_14    svc:/network/ipsec/
ipsealgs:default
online          Jan_14    svc:/system/boot-archive:default
online          Jan_14    svc:/system/filesystem/
usr:default
online          Jan_14    svc:/system/device/local:default
online          Jan_14    svc:/system/filesystem/
minimal:default
online          Jan_14    svc:/system/identity:domain
[...]
```

Press **q** when you reach to the end of the list to exit. Same way when you want to find out all the services that are not running, replace **online** with **offline** in **grep**.

To enable apache (if you have installed **amp-dev** package) service

```
$ pfexec svcadm enable svc:/network/http:apache22
```

To disable, replace **enable** with **disable**.

To display the status of a current service execute **svcs -l** command. For example:

```
$ svcs -l svc:/network/http:apache22
fmri          svc:/network/http:apache22
name          Apache 2.2 HTTP server
```