

	NAME USED	AVAIL	REFER	MOUNTPPOINT	
	tank/home@now		0		-
29.5K		-			
	tank/home/ahrens@now		0	-	2.15M
-					
	tank/home/anne@now		0	-	1.89M
-					
	tank/home/bob@now		0		-
1.89M		-			
	tank/home/cindys@now		0		-
2.15M		-			

Snapshots have no modifiable properties, nor can dataset properties be applied to a snapshot.

```
# zfs set compression=on tank/home/ahrens@tuesday
cannot set compression property for 'tank/home/ahrens@tuesday': snapshot properties cannot be modified
```

Snapshots are destroyed by using the `zfs destroy` command. For example:

```
# zfs destroy tank/home/ahrens@friday
```

A dataset cannot be destroyed if snapshots of the dataset exist. For example:

```
# zfs destroy tank/home/ahrens
cannot destroy 'tank/home/ahrens': filesystem has children
```

use `'-r'` to destroy the following datasets:

```
tank/home/ahrens@tuesday
tank/home/ahrens@wednesday
tank/home/ahrens@thursday
```

In addition, if clones have been created from a snapshot, then they must be destroyed before the snapshot can be destroyed.

4.9.2 Holding ZFS snapshots

If you have different automatic snapshot policies so that older snapshots are being inadvertently destroyed by ZFS receive because they no longer exist on the sending side, you might consider using the snapshots hold feature. Holding a snapshot prevents it from being destroyed. In addition, this feature allows a snapshot with clones to be deleted pending the removal of the last clone by using the `ZFS destroy -d` command. Each snapshot has an associated user-reference count, which is initialised to zero. This count