

within the root of the containing file system. For example, if `tank/home/ahrens` is mounted on `/home/ahrens`, then the `tank/home/ahrens@thursday` snapshot data is accessible in the `/home/ahrens/.zfs/snapshot/thursday` directory.

```
# ls /tank/home/ahrens/.zfs/snapshot
tuesday wednesday thursday
# zfs list -t snapshot
NAME                USED  AVAIL  REFER  MOUNTPOINT
pool/home/anne@monday      0      -
780K  -
pool/home/bob@monday      0      -
1.01M  -
tank/home/ahrens@tuesday    8.50K  -
780K  -
tank/home/ahrens@wednesday  8.50K  -
1.01M  -
tank/home/ahrens@thursday    0      -
1.77M  -
tank/home/cindys@today     8.50K  -
524K  -
```

You can list snapshots that were created for a particular file system as follows:

```
# zfs list -r -t snapshot -o name,creation tank/home
NAME                                CREATION
tank/home/ahrens@tuesday            Mon Aug 31
11:03 2009
tank/home/ahrens@wednesday          Mon Aug 31 11:03 2009
tank/home/ahrens@thursday           Mon Aug 31
11:03 2009
tank/home/cindys@now                 Mon Aug 31
11:04 2009
```

4.9.5 Snapshot space accounting

When a snapshot is created, its space is initially shared between the snapshot and the file system, and possibly with previous snapshots. As the file system changes, space that was previously shared becomes unique to the snapshot, and thus is counted in the snapshot's used property.

Additionally, deleting snapshots can increase the amount of space unique